

3 STRAND TWISTED NYLON

A VERSATILE HARD WORKING LINE FOR A VARIETY OF APPLICATIONS



<i>DIA</i>	<i>CIRC</i>	<i>LBS/100'</i>	<i>AVG REAK STRENGTH (lbs)</i>	<i>WORKING LOAD LIMITS (lbs) 1/12 - 1/5</i>
3/8"	1-1/8"	3.50	3,300	275 - 660
1/2"	1-1/2"	6.51	5,760	480 - 1152
5/8"	2"	10.30	9,360	780 - 1872
3/4"	2-1/4"	14.80	12,750	1063 - 2550

- ◇ Excellent shock absorption characteristics
 - ◇ Mooring and Anchor lines
 - ◇ Safety Lanyards



P/D 100™

A SPECIAL COMBINATION ROPE BLENDING THE MOST COMPATIBLE AND UNIQUE CHARACTERISTICS OF POLYESTER & POLYPROPYLENE SYNTHETIC FIBERS.

3 STRAND CONSTRUCTION

DIA	CIRC	LBS/100'	AVG REAK STRENGTH (lbs)	WORKING LOAD LIMITS (lbs) 1/12 - 1/5
3/8"	1-1/8"	3.82	2520	210 - 504
1/2"	1-1/2"	6.36	3,960	330 - 792
5/8"	2"	8.96	6,600	550 - 550
3/4"	2-1/4"	13.0	9,000	750 - 1800

PD100 is known for the Lineman Rodeo rope and as an all around hand line for hauling tools, tying off conductors, guying, lifting, and lowering in single blocks.

- Good Grip
- Good Wear Resistance
- Good Knot-Holding Qualities

Monofilament Polypropylene Jacketed with Filament Polyester



8 STRAND CONSTRUCTION

DIA	CIRC	LBS/100'	MIN BREAK STRENGTH (lbs)	WORKING LOAD LIMITS (lbs) 1/12 - 1/5
3/8"	1-1/8"	3.82	2700	225 - 540
1/2"	1-1/2"	6.36	4,500	375 - 900
5/8"	2"	8.96	7,000	583 - 1400
3/4"	2-1/4"	13.0	9,200	766 - 1840
7/8"	2-3/4"	18.3	12,800	1066 - 2560
1"	3"	21.1	15,600	1300 - 3120
1-1/8"	3-1/2"	27.5	19,300	1608 - 3860
1-1/4"	3-3/4"	31.7	22,500	1875 - 4500

Available in 8 Strand Plimoor® Construction to prevent kinking or hockling of the line.

Larger diameters for use as *Bull Ropes* for Guying, Setting Poles, Hoisting Transformers, Towing and Short Line Stringing.

P/D 100™ the unique, smooth-working aptitude required for use over capstans and winch heads.

