

MIL-R-24537 (SH) ROPE, FIBROUS, PLAITED, CONTINUOUS FILAMENT w/STAPLE WRAP is a 8 Strand Plaited fiber rope often used as a component of rigs used in fueling at sea (FAS) and replenishment at sea (RAS).** The rope is constructed from virgin, continuous filament, heat and light resistant polyester filament with a staple wrap.

8 Strand Plaited DACRON® POLYESTER MIL-R-24537 (SH)			
<i>DIA</i>	<i>CIRC</i>	<i>LBS/100'</i>	MINIMUM BREAK STRENGTH
3/8"	1 1/8"	4.35 lbs.	3,970 lbs.
1/2"	1 1/2"	7.35 lbs.	6,400 lbs.
5/8"	2"	12.20 lbs.	9,900 lbs.
3/4"	2 1/4"	15.20 lbs.	12,200 lbs.
7/8"	2-3/4"	21.5 lbs.	16,700 lbs.
1"	3"	25.2 lbs.	19,000 lbs.
1 1/8"	3 1/2"	33.60 lbs.	25,000 lbs.
1 1/4"	3 3/4"	37.80 lbs.	27,500 lbs.
1 5/16"	4"	42.5 lbs.	30,700 lbs.
1 1/2"	4 1/2"	63.00 lbs.	37,000 lbs.

** See Naval Warfare Publication NWP 4-01.4, UNDERWAY REPLENISHMENT for further details.